

LRM-10™

Automatic Digital Micro-Ohmmeter

The LRM-10™ is a fully automatic digital micro-ohmmeter, auto-scale selecting up to 10A DC for ultra-accurate resistance readings from 0.01 $\mu\Omega$ to 200 Ω . Built into a rugged and lightweight case, the LRM-10™ is the perfect tool for field and laboratory tasks.

Highlights

- Ultra accurate readings, best in class
- Four-lead Kelvin method
- Highly filtered input channels
- Long lasting, rechargeable batteries
- Array of probes available
- Custom probes are available
- Standard & differential operation modes
- Trusted worldwide since 1999
- Very easy to use



Small Package, Big Performances

- LRM-10™ is a high-quality, well-thought micro-ohmmeter kit that offer high accuracy and portability
- Finally able to confidently measure very low resistance either at job site, or in the lab with consistent results
- With its highly filtered input channels, the LRM-10™ allows precise measurements even in presence of intense magnetic field
- LRM-10™, Accurate, Portable and Reliable

Free interactive presentation:



[Click here to schedule](#)



sales@ndbtech.com



ndbtech.com



Technical Specifications

Measuring range	0.01 $\mu\Omega$ to 200 Ω
Display	LCD display, 128 x 64 pixels
Current	10A, 250mA, 5mA
Resolution	0.01 $\mu\Omega$
Power Supply	Six AA NiMH batteries
Autonomy	> 12 000 measurements at 10A > 10 000 measurements for the other currents
Operation temperature	-20°C to 50°C (-4°F to 122°F)
Charging temperature	0°C to 50°C (32°F to 122°F)
Storage temperature	-40°C to 50°C (-40°F to 122°F)
Protection rating	IP54
Humidity	0 to 95% non-condensing
Weight	0.86 kg (1.9 lbs)
Dimensions	203 x 114 x 51mm (8 x 4.5 x 2 inches)



Well suited for circuit breaker contacts testing

LRM-10™ kit includes:

- LRM-10 micro-ohmmeter
- Nylon protective bag
- Set of standard cable & clips
- Set of heavy-duty double hand probes
- NiMH rechargeable batteries
- Battery charger
- User manual
- Calibration certificate

Booster Type Clamps

The DRM-4017-35™ booster type clamps are designed for low resistance measurement on various contact type devices. It offers an opening of 35mm (1.37 inches) and a sturdy design suited for field application.



Dolphin Type Clamps

The DRM-4017-19™ dolphin type clips are designed for low resistance measurement on various contact type devices. It offers an opening of 19mm (0.67 inches).



Cadweld Probe

The DRM-4012™ probe is specifically designed for non-destructive testing of exothermic Cadweld bonds typically found in substations.



Transportation Case

The BOX-075™ transportation case allows to protect your LRM-10 instrument while working in the field. Fully made of synthetic materials, this case offers plenty of space for all your LRM accessories.

